

PAPER CUTTERS

	TITAN 265	TITAN 230	TITAN 200
Maximum Cutting Width	26-1/2" / 67.3 cm	23" / 58.4 cm	20" / 50.8 cm
Minimum Cut: without false clamp plate with false clamp plate	5/8" / 16 mm 1-7/8" / 48 mm	1/2" / 13 mm 1-7/8" / 48 mm	1/2" / 13 mm 1-7/8" / 48 mm
Maximum Cut Depth	28" / 71.1 cm	24" / 61.0 cm	20" / 50.8 cm
Clamp Opening: without false clamp plate with false clamp plate	4" / 10.2 cm 3-3/4" / 9.5 cm	3-1/4" / 8.3 cm 3" / 7.6 cm	3-1/4" / 8.3 cm 3" / 7.6 cm
Clamp Force: minimum maximum	1,470 lbs / 652 daN 4,000 lbs / 1,800 daN	1,250 lbs / 563 daN 2,500 lbs / 1,125 daN	1,250 lbs / 563 daN 2,500 lbs / 1,125 daN
Clamping Method Backgauge Control	Hydraulic & Power Soft Clamp Power	Hydraulic & Manual Power	Hydraulic & Manual Power
Knife Cycle Speed	26 cuts/min	20 cuts/min	20 cuts/min

DIMENSIONS

Table Space: in front of knife	24-1/2" / 62 cm	24-1/4" / 61.6 cm	15-1/4" / 38.7 cm
Overall Height	60-1/3" / 153 cm	53" / 135 cm	53" / 135 cm
Overall Width	54" / 137 cm	50" / 127 cm	36" / 92 cm
Overall Length	70-1/3" / 179 cm	66" / 168 cm	50-7/8" / 129 cm
Side Tables Optional Side Tables	13-1/2" x 16" / 34.3 x 40.6 cm	13-1/2" x 16" / 34.3 x 40.6 cm 18"x20" / 46 x 51 cm	8-1/4" x 12-1/4" / 21 x 31 cm
Minimum opening required thru door: Table, treadle & light beam off:	54" / 137 cm 31" / 79 cm	43" / 109 cm 29" / 74 cm	36-1/4" / 92 cm* 29" / 74 cm
Net Weight (approximate)	1780 lbs / 808 kg	1000 lbs / 454 kg	800 lbs / 363 kg
Shipping Weight (approximate)	2020 lbs / 917 kg	1250 lbs / 567 kg	980 lbs / 444 kg

ELECTRICAL CE

Titan 265 Motor 5 H.P., 208/230 Volts, 60 Hz, 3 Phase, AC, 25 Amps. Service size 30 Amps.
Single Phase Supply Kit: K-3482

Optional Motors: 5 H.P., 380/415 Volts, 50 Hz, 3 Phase, AC, 15 Amps. Service size 20 Amps.

Titan 230 Motor 1-1/2H.P., 230 Volts, 60 Hz, 1 Phase, AC, 12 Amps. Service size 15 Amps. Requires receptacle type: NEMA6-15R or 6-20R. (Optional 50 Hz, 1 phase available)

Titan 200 Motor 1-1/2H.P., 230 Volts, 60 Hz, 1 Phase, AC, 12 Amps. Service size 15 Amps. Requires receptacle type: NEMA6-15R or 6-20R. (Optional 50 Hz, 1 phase available)

Challenge reserves the right to make changes to any product or specification without notice and without incurring responsibility to existing units.
Challenge and Titan are registered trademarks of The Challenge Machinery Company.



THE CHALLENGE MACHINERY COMPANY
6125 Norton Center Dr. Norton Shores, MI 49441 USA
Phone: 231.799.8484 Fax: 231.798.1275
www.challengemachinery.com



**ASSURANCE YOU MADE
THE RIGHT DECISION**